

RESINOVA - USE IN CONSTRUCTION

BONDITITE METALIC
used in weld joints and on rusted surface

BONDCRETE WATER REPELLENT
used for water repelency to varied surfaces like sand stone, Marble, concrete, exposed bricks and terrakota tiles

BONDITITE WHITE PASTE
used to paste Marble on concrete

BONDCRETE Two Component
used for grouting steel railing on concrete slab & to maintain natural colour

BONDCRETE (Water thinable sealer)
used to keep outer wall moisture free & to maintain Glossy finish . It can be applied using Brush.

BONDITITE WOOD
High strength adhesive for bonding wood to wood & metal. Excellent system for wood repair and rebuilding work

ZIRMEK
used for fixing ceramic tiles, wooden moldings on vertical surface.It is fast drying and poses very high flexibility.



RESIZEN
for installation of wall and floor panels, for bonding wood, metal, Glass, cement concrete, plaster sheets, hard plastics etc

BONDITITE GEL
for coating on tile joints to avoid color change of grout on repetitive cleaning.Colours can be added to give desired effect on textile, glass and wooden surfaces

BONDCRETE (WATER PROOFING COMPOUND)
to be applied over exterior surface of walls to prevent entry of water and moisture from the surface

CRACKBOND POINTING
for filling joints of marble flooring in place of white cement. After curing this system gets converted to marble white colour

RESIBOND
Used in glass sealing , to prevent water entry from windows

ZESTA 666
Single component white emulsion adhesive for wood working and general bonding applications.

GINEE CORPORATION